

SMART PUBLIC DC CHARGER 40 kW, 3-phase, wall-mounted



CONVENIENT

7" touch screen LCD for parameter browsing and setting



RELIABLE

IP54 protection for outdoor installation



GLOBAL STANDARD

OCPP v1.6 open charge point protocol. IEC 62196 type II connector



EASY TO INSTALL

Wall-mounting or pole-mounting



CAPABLE

Option with 1 or 2 CCS Plugs, more efficient charging, option with CCS and CHAdeMO



FLEXIBLE

25 - 40 kW power control




CERTIFICATION

Certificate CE



MECHANICAL

Dimension (W/H/D) 556 / 775 / 270 mm
Weight <78 KG



SMART PUBLIC DC CHARGER 40 kW, 3-phase, wall-mounted

<p>Input & Output</p> <p>Input voltage Frequency DC plug type Output voltage range Output current Voltage accuracy Current-regulating accuracy Metering accuracy Connection Voltage-regulating accuracy Ripple coefficient Efficiency</p>	<p>260–530V AC 50/60Hz 1x CCS / 2x CCS / 1x CCS + 1x CHAdeMO 150-750V DC 0-33,3A / 0-60A / per phase $\leq \pm 1\%$ $\leq \pm 1\%$ 0.5% Integrated 5m cables $\leq \pm 0.5\%$ $\leq \pm 1\%$ $\geq 95.2\%$</p>
<p>Protection</p> <p>Over voltage protection Under voltage protection Overload protection Leakage current protection Overtemperature protection Under temperature protection Surge protection</p>	<p>Yes Yes Yes Yes Yes Yes Yes</p>
<p>Function & Accessory</p> <p>Ethernet / WIFI / 4G Display Indicator Payment support Emergency stop Cable Length RFID Load Balancing distance</p>	<p>Yes / Opt / Yes 7 inch touch screen Yes RFID / QR (standard) Free / APP Mega Mobility Yes 5 m Yes >15 m (3PHM)</p>
<p>Working environment</p> <p>Protection degree Environment temperature Relative humidity Maximum altitude Cooling Standby power Noise emission</p>	<p>IP54 -25°C ~ +50°C 5 – 95% non-condensing <2000 m Forced air cooling <25W $\leq 65\text{db}$</p>
<p>Mechanical</p> <p>Dimension (W / H / D) Weight</p>	<p>540 / 760 / 271 mm <78 kg</p>
<p>Certification</p> <p>Certificate</p>	<p>CE</p>

